Amendments to the Claims

1. (Currently Amended) An artificial cover for covering an underlying structure, comprising:

a first side with a three-dimensional rock pattern protruding from the first side, wherein the three-dimensional rock pattern includes a plurality of three dimensional rock-shaped protrusions extending from the first side at acute angles;

a second side configured to contact and attach to the underlying structure; and a colorant disposed in a surface skin of the three-dimensional rock pattern, the colorant incorporated as part of a matrix of the artificial cover;

wherein the artificial cover has a sufficient rigidity to prevent sagging upon securing the artificial cover to the underlying structure;

wherein the artificial cover does not include a reinforcing liner in the matrix of the artificial cover.

- 2. (Previously Presented) The artificial cover according to claim 1, wherein the artificial cover comprises a material selected from the group consisting of: polyurethane, plastic, rubber, fiberglass, and carbon fiber.
- 3. (Original) The artificial cover according to claim 1, wherein the underlying structure is a foundation of a home.

- 4. (Original) The artificial cover according to claim 1, wherein the underlying structure is . a stair case.
- 5. (Original) The artificial cover according to claim 1, wherein the artificial cover attaches to the underlying structure with screws.
- 6. (Canceled)
- 7. (Canceled)
- 8. (Canceled)
- 9. (Canceled)
- 10. (Canceled)
- 11. (Canceled)
- 12. (Canceled)
- 13. (Canceled)
- 14. (Canceled)
- 15. (Canceled)
- 16. (Canceled)
- 17. (Canceled)
- 18. (Canceled)
- 19. (Canceled)
- 20. (Canceled)

- 21. (Previously Presented) The artificial cover according to claim 1, wherein the upper portions of the three dimensional rock-shaped protrusions extend from the first side at acute angles.
- 22. (Currently Amended) An artificial cover for covering an underlying structure, comprising:
- a first side with a three-dimensional rock pattern protruding from the first side,;
- a second side configured to contact and attach to the underlying structure; and a colorant disposed in a surface skin of the three-dimensional rock pattern, the colorant incorporated as part of a matrix of the artificial cover;

wherein the artificial cover has a sufficient rigidity to prevent sagging upon securing the artificial cover to the underlying structure;

wherein the artificial cover does not include a reinforcing liner in the matrix of the artificial cover.

- 23. (Previously Presented) The artificial cover of claim 22, wherein the threedimensional rock pattern includes a plurality of three dimensional rock-shaped protrusions extending from first side, wherein the upper portion of the three dimensional rock-shaped protrusions extend outward at acute angles.
- 24. (Previously Presented) The artificial cover according to claim 22, wherein the artificial cover comprises material selected from the group consisting of: polyurethane,

01/30/2008 09:39

plastic, rubber, fiberglass, and carbon fiber.

- 25. (Previously Presented) The artificial cover according to claim 22, wherein the underlying structure is selected from the group consisting of: a foundation of a home, a staircase, and any combinations thereof.
- 26. (Previously Presented) The artificial cover according to claim 1, wherein the artificial cover attaches to the underlying structure with screws.
- 27. (Withdrawn) The method of claim 12, before coating the mold with the urethane release, further comprising forming the mold such that the three-dimensional rock pattern includes a plurality of rock-shaped protrusions extending from the artificial cover at acute angles.
- 28. (Withdrawn) The method of claim 27, wherein the upper portions of the rock-shaped protrusions extend outward at acute angles.
- 29. (Withdrawn) A method for forming an artificial cover, configured to be secured to an underlying structure, comprising the steps of:

coating a three dimensional rock pattern mold with a urethane release;

introducing a colorant to the mold to give the pattern a natural look;

applying sufficient polyurethane to the mold such the artificial cover includes structural integrity sufficient to prevent sagging when secured to the underlying structure; and

curing the mold such that the colorant is incorporated into the matrix of the polyurethane.

removing the artificial cover from the mold.

- 30. (Withdrawn) The method of claim 29, further comprising touching up imperfections in the artificial cover.
- 31. (Withdrawn) The method of claim 30, further comprising coating the artificial cover with a protective coating.
- 32. (Withdrawn) The method of claim 31, wherein the protective coating comprises a polyurethane ultraviolet layer
- 33. (Withdrawn) The method of claim 31, further comprising cutting the artificial cover according to measured dimensions.
- 34. (Withdrawn) The method of claim 29, wherein the colorant comprises an alkyd based paint.

From: Starkweather & Associates 8017481030 01/30/2008 09:39 #707 P. 011/015

App. No. 10/827,468 Attorney Docket 3053.2.2np

Amendments to the Drawings

None